



TR 118 - Ficha técnica

Description

TR 118 ha sido proyectado para máquinas de riego. TR 118 se caracteriza por una carcasa reforzada y un número mayor de tacos que aseguran una vida operativa más larga del neumático.



UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Equipo de riego a pivote

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
14.9 - 24	STANDARD	R1	128 A6	8	W 13	W 12 ; W 11	380	1265	566	3742	600	TL	E11-106R-004420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 10:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..