

TR 135 - Especificaciones técnicas



Description

TR 135 es idóneo para tractores en los trabajos del campo. La carcasa reforzada y la mezcla particularmente resistente a los cortes y los desgarres proporcionan un ciclo de vida más largo. Sus óptimas prestaciones de tracción, auto limpieza y estabilidad, son las características clave que hacen que TR 135 sea el neumático ideal, incluso en las condiciones más difíciles del terreno.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Tractor
Industrial: Remolque

Version	STANDARD
Type	TT
Tyre Size	23.1 - 34
LI/SS	153 A6

Dimensions International Standard

Ply Rating	10
Section Width (mm)	585
Overall Diameter (mm)	1810
Static Loaded Radius (mm)	834
Rolling Circumference (mm)	5321
Rim Rec	DW 20 B ; DW 20 A
ECE	E4-106R-002831
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.40
30	3650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 11:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..