

## TR 137 - Especificaciones técnicas



### Description

TR 137 es el neumático ideal para todas las operaciones de recogida, ya que asegura una excelente tracción en el campo incluso a cargas elevadas. Este neumático está disponible en diferentes versiones: la versión "aramid-belted", con cinturones de aramida, garantiza una mejor resistencia a la perforación y protección contra los daños típicos de esta actividad; la versión "HD" ofrece una extraordinaria resistencia a los cortes y los desgarres, así como un ciclo de vida más largo.

### UM

International Standard

### Construction

✦ BIAS

### Machinery

Agricultura: Cosechadora

Version	HD
Type	TL
Tyre Size	30.5L - 32
LI/SS	170 A6

## Dimensions International Standard

Ply Rating	18
Section Width (mm)	770
Overall Diameter (mm)	1865
Static Loaded Radius (mm)	831
Rolling Circumference (mm)	5520
Rim Rec	DH 27 B
Rim Alt	DW 27 B
ECE	E4-106R-002283
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.10
30	6000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..