

TR 315 - Especificaciones técnicas



Description

TR 315 es un neumático para el césped y la jardinería, idóneo para las operaciones en los segmentos de municipalidad/mantenimiento. Este neumático es ideal para utilizarlo con la maquinaria agrícola, las zanjadoras y las máquinas para la recogida de fruta. TR 315 presenta una amplia área de contacto que proporciona un excelente agarre, así como una extraordinaria estabilidad en cualquier condición y óptimas propiedades de auto-limpieza.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Máquina para la recogida de fruta • Zanjadora

Version	STANDARD
Type	TL
Tyre Size	31 X 15.50 - 15

Dimensions International Standard

Ply Rating	12
Section Width (mm)	390
Overall Diameter (mm)	800
Static Loaded Radius (mm)	354
Rolling Circumference (mm)	2320
Rim Rec	13 LB
ECE	E4-106R-002333

Load capacity (Kg)

km/h / bar	5.10
50	1650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 16:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..