

TR 315 - Ficha técnica



Description

TR 315 es un neumático para el césped y la jardinería, idóneo para las operaciones en los segmentos de municipalidad/mantenimiento. Este neumático es ideal para utilizarlo con la maquinaria agrícola, las zanjadoras y las máquinas para la recogida de fruta. TR 315 presenta una amplia área de contacto que proporciona un excelente agarre, así como una extraordinaria estabilidad en cualquier condición y óptimas propiedades de auto-limpieza.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Maquina para la recogida de fruta • Zanjadora

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
16 X 6.50 - 8	STANDARD	94022250	4	5.375 I - 55 ; I - 70 ; I - 90		6.1	16.1	7.2	46.6	TL	E11-106R-003493
16 X 6.50 - 8	STANDARD	94022274	6	5.375 I - 55 ; I - 70 ; I - 90		6.1	16.1	7.2	46.6	TL	E4-106R-002175
23 X 10.50 - 12	STANDARD	94022298	4	8½ JA	7 JA	10	23.6	10.7	72.4	TL	E4-106R-002179
23 X 10.50 - 12	STANDARD	94022311	6	8½ JA	7 JA	10	23.6	10.7	72.4	TL	E4-106R-002177
23 X 10.50 - 12	STANDARD	94028436	8	8½ JA	7 JA	10	23.6	10.7	72.4	TL	E4-106R-002661
23 X 10.50 - 12	STANDARD	94027873	10	8½ JA	7 JA	10	23.6	10.7	72.4	TL	E11-106R-005206
23 X 10.50 - 12	STANDARD	94070381	12	8½ JA	7 JA	10	23.6	10.7	72.4	TL	E11-106R-007639
23 X 8.50 - 12	STANDARD	94022335	4	7 JA ; 7.00 I - 55 ; I - 70 ; I - 90		8.1	22.6	10.2	65.7	TL	E11-106R-004518
23 X 8.50 - 12	STANDARD	94022359	6	7 JA ; 7.00 I - 55 ; I - 70 ; I - 90		8.1	22.6	10.2	65.7	TL	E4-106R-002178
26 X 12.00 - 12	SPECIAL	94038169	10	10½ JA	8½ JA ; 9½ JA	12.1	25.8	11.4	75	TL	E11-106R-004519
26 X 12.00 - 12	STANDARD	94022373	4	10½ JA	8½ JA ; 9½ JA	12.1	25.8	11.4	75	TL	E11-106R-003494
26 X 12.00 - 12	STANDARD	94022410	8	10½ JA	8½ JA ; 9½ JA	12.1	25.8	11.4	75	TL	E4-106R-002674
26 X 12.00 - 12	STANDARD	94036592	10	10½ JA	8½ JA ; 9½ JA	12.1	25.8	11.4	75	TL	E11-106R-004519
26 X 12.00 - 12	STANDARD	94022397	12	10½ JA	8½ JA ; 9½ JA	12.1	25.8	11.4	75	TL	E4-106R-002328
31 X 15.50 - 15	STANDARD	94022441	8	13 LB		15.4	31.5	13.9	91.3	TL	E4-106R-002208
31 X 15.50 - 15	STANDARD	94043774	10	13 LB		15.4	31.5	13.9	91.3	TL	E4-106R-001553
31 X 15.50 - 15	STANDARD	94044740	12	13 LB		15.4	31.5	13.9	91.3	TL	E4-106R-002333

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..