

TR 318 - Especificaciones técnicas



Description

TR 318 está especialmente proyectado para los pulverizadores y maquinaria agrícola. Los tacos de doble ángulo aseguran una excelente tracción y un extraordinario confort de guía. TR 318 ofrece además óptimas cualidades de auto-limpieza.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Pulverizador

Version	STANDARD
Type	TL
Tyre Size	23 X 9.00 - 12
LI/SS	93 A3

Dimensions US Standard

Usa code	94070428
Ply Rating	6
Section Width (inch)	8.7
Overall Diameter (inch)	23
Rim Rec	7.0
ECE	E11-106R-004521

Load capacity (lbs)

mph / psi	43
10	1433

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 4:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..