

TR 319 - Ficha técnica



Description

TR 319 es un neumático que se utiliza en la maquinaria agrícola, como en las máquinas para la recogida de fruta y las zanjadoras destinadas tanto a los trabajos de jardinería como del campo y en los segmentos de municipalidad/mantenimiento. Este neumático muestra una amplia área de contacto que se traduce en una óptima tracción. Por tanto, TR 319 es idóneo para usarlo en superficies tanto mojadas, cuando se requiere estabilidad y propiedades de auto-limpieza.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Maquinaria agrícola • Máquina para la recogida de fruta • Zanjadora

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
26 X 12.00 - 12	STANDARD	116 A3	8	10.50 AT	8.0 AT ; 8.5 AT ; 9.0 AT	318	640	290	1908	TL	E11-106R-003560
29 X 12.50 - 15	STANDARD	106 B	8	10 LB		312	755	360	2264	TL	E11-106R-004605
29 X 12.50 - 15	STANDARD	98 B	6	10 LB		312	755	360	2264	TL	E11-106R-004604

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 12:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..