

TR 387 IND - Especificaciones técnicas



Description

TR 387 IND es un neumático industrial, idóneo para los remolques industriales y compactadores. Este neumático se caracteriza por una elevada capacidad de carga y está disponible en diferentes versiones con el fin de satisfacer las exigencias específicas de los usuarios en términos de resistencia a los cortes y los desgarres, trabajos pesados y durabilidad. La versión "dual bead", de doble talón, es particularmente idónea para los tractores industriales y las operaciones de transporte con remolques.

UM

US Standard

Construction

❖ BIAS

Machinery

Industrial: Compactador • Tractor • Remolque

Version	DUAL BEAD HD
Type	TL
Tyre Size	24.5 - 32
LI/SS	160 A8

Dimensions US Standard

Usa code	94057702
Ply Rating	16
Section Width (inch)	24.6
Overall Diameter (inch)	69.1
Static Loaded Radius (inch)	31.1
Rolling Circumference (inch)	205.7
Rim Rec	DH 21
Rim Alt	DH 21 B ; DH 21 H ; DH 21 HB
TRA Code	R3

Load capacity (lbs)

mph / psi	30
25	9900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 13:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..