

TR 387 - Especificaciones técnicas



Description

TR 387 es un neumático agro-industrial, idóneo para los remolques que transportan la caña da azúcar y los compactadores. Este neumático se caracteriza por una elevada capacidad de carga y está disponible en diferentes versiones con el fin de satisfacer las exigencias específicas de los usuarios en términos de resistencia a los cortes y los desgarres, trabajos pesados y durabilidad. La versión "dual bead", de doble talón, es particularmente idónea para los tractores industriales y las operaciones de transporte con remolques.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Remolque

Industrial: Compactador

Version	STANDARD
Type	TL
Tyre Size	16.9 - 30 (14 - 30)
LI/SS	137 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	440
Overall Diameter (mm)	1450
Static Loaded Radius (mm)	655
Rolling Circumference (mm)	4220
Rim Rec	DW 15 L
Rim Alt	DW 14 L
ECE	E11-106R-005279
TRA Code	R3

Load capacity (Kg)

km/h / bar	1.70
30	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 5:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..