

TR 459 - Especificaciones técnicas



Description

TR 459 ha sido específicamente proyectado para las operaciones de excavación y de carga, así como los trabajos realizados en el sector de la municipalidad y el mantenimiento con tractores y ternas. Este neumático ofrece una elevada estabilidad y está disponible en dos versiones. La versión "special" garantiza un ciclo de vida prolongado del neumático.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Cargadora retroexcavadora • Tractor
Industrial: Cargadora retroexcavadora

Version	INDUSTRIAL
Type	TL
Tyre Size	14.9 - 24
LI/SS	137 A8

Dimensions US Standard

Usa code	94016440
Ply Rating	8
Section Width (inch)	15.4
Overall Diameter (inch)	49
Static Loaded Radius (inch)	22.1
Rolling Circumference (inch)	144
Rim Rec	DW 13
Rim Alt	DW 12 ; DW 11 ; DW 13 L
ECE	E11-106R-005281
TRA Code	R4

Load capacity (lbs)

	mph / psi	30
	25	5080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..