

TR 459 - Ficha técnica



Description

TR 459 ha sido específicamente proyectado para las operaciones de excavación y de carga, así como los trabajos realizados en el sector de la municipalidad y el mantenimiento con tractores y ternas. Este neumático ofrece una elevada estabilidad y está disponible en dos versiones. La versión "special" garantiza un ciclo de vida prolongado del neumático.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Cargadora retroexcavadora • Tractor
Industrial: Cargadora retroexcavadora

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
400/70 - 20	INDUSTRIAL	R4	149 A8		13	12 SDC ; 13 SDC ; 14	404	1090	0	0	TL	E11-106R-005332
14.9 - 24	INDUSTRIAL	R4	137 A8	8	DW 13	DW 12 ; DW 11 ; DW 13 L	390	1244	562	3657	TL	E11-106R-005281
14.9 - 24	INDUSTRIAL	R4	145 A8	12	DW 13	DW 12 ; DW 11 ; DW 13 L	390	1244	562	3657	TL	E11-106R-005333
16.9 - 24	INDUSTRIAL	R4	142 A8	8	DW 15 L	DW 14 L	450	1310	590	3850	TL	E11-106R-005188
16.9 - 24	INDUSTRIAL	R4	145 A8	10	DW 15 L	DW 14 L	450	1310	590	3850	TL	E11-106R-005211
16.9 - 24	INDUSTRIAL	R4	149 A8	12	DW 15 L	DW 14 L	450	1310	590	3850	TL	E11-106R-003624
17.5L - 24	INDUSTRIAL	R4	139 A8	8	DW 15 L	DW 14 L	445	1270	557	3825	TL	E11-106R-005212
17.5L - 24	INDUSTRIAL	R4	144 A8	10	DW 15 L	DW 14 L	445	1270	557	3825	TL	E11-106R-005285
17.5L - 24	INDUSTRIAL	R4	148 A8	12	DW 15 L	DW 14 L	445	1270	557	3825	TL	E11-106R-004659
18.4 - 24	INDUSTRIAL	R4	155 A8	12	DW 16 L	DW 15 L	472	1375	610	4114	TL	E11-106R-005217
19.5L - 24	INDUSTRIAL	R4	147 A8	10	DW 16 L		490	1333	585	4031	TL	E11-106R-005334
19.5L - 24	INDUSTRIAL	R4	151 A8	12	DW 16 L		490	1333	585	4031	TL	E4-106R-002300
19.5L - 24	INDUSTRIAL SPECIAL	R4	151 A8	12	DW 16 L		490	1333	585	4031	TL	
21L - 24	INDUSTRIAL	R4	155 A8	12	DW 18 L		533	1378	605	3995	TL	E11-106R-003625
21L - 24	INDUSTRIAL	R4	157 A8	14	DW 18 L		533	1378	605	3995	TL	E11-106R-005366
18.4 - 26	INDUSTRIAL	R4	156 A8	12	DW 16 L	DW 15 L	472	1425	628	4346	TL	E4-106R-002304
18.4 - 26	INDUSTRIAL	R4	159 A8	14	DW 16 L	DW 15 L	472	1425	628	4346	TL	E11-106R-003396
18.4 - 26	INDUSTRIAL	R4	162 A8	16	DW 16 L	DW 15 L	472	1425	628	4346	TL	E11-106R-006635
16.9 - 28	INDUSTRIAL	R4	145 A8	8	DW 15 L	DW 14 L	440	1410	640	4145	TL	E11-106R-005287
16.9 - 28	INDUSTRIAL	R4	148 A8	10	DW 15 L	DW 14 L	440	1410	640	4145	TL	E11-106R-005451
16.9 - 28	INDUSTRIAL	R4	152 A8	12	DW 15 L	DW 14 L	440	1410	640	4145	TL	E11-106R-003626
18.4 - 28	INDUSTRIAL	R4	157 A8	12	DW 16 L	DW 15 L	472	1475	664	4495	TL	E4-106R-002830
21L - 28	INDUSTRIAL	R4	157 A8	12	DW 18 A		535	1480	0	0	TL	E11-106R-005335
16.9 - 30	INDUSTRIAL	R4	153 A8	12	DW 15 L	DW 14 L	440	1470	657	4484	TL	E11-106R-005288

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..