

## TR 678 - Especificaciones técnicas



### Description

TR 678 ha sido particularmente desarrollado para las aplicaciones forestales. El robusto dibujo de los tacos garantiza una excelente tracción y auto-limpieza. La tenaz estructura de la carcasa se traduce en una elevada capacidad de carga, mientras que los cinturones de acero protegen el neumático contra los pinchazos y otros daños. TR 678 se caracteriza por una mezcla resistente a los cortes que garantiza, incluso en terrenos difíciles y en condiciones extremas, una excelente resistencia a los cortes y las roturas.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Agricultura: Maquinaria agrícola • Remolque  
Industrial: Pala excavadora • Remolque

Version	STEEL BELTED
Type	TL
Tyre Size	600/55 - 26.5
LI/SS	172 A2 / 165 A8

## Dimensions US Standard

Usa code	94074112
Ply Rating	20
Section Width (inch)	23.8
Overall Diameter (inch)	53.1
Rim Rec	AG 20.00
ECE	E11-106R-008132
TRA Code	LS2

## Load capacity (lbs)

mph / psi	80
25	11355
5	13890

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 17:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..