

TRAC SUPER - Especificaciones técnicas



Description

TRAC SUPER es el primer neumático radial introducido por BKT en el segmento de la municipalidad. La estructura del neumático con cinturones de acero asegura una óptima conducción lisa, combinada con las mejores prestaciones de tracción. Por tanto, este neumático es particularmente idóneo para trabajar en superficies de amplios prados, como en los parques y a lo largo de las carreteras.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Minitractor

| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 500/50 R 17 |
| LI/SS | 147 D |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 490 |
| Overall Diameter (mm) | 940 |
| Static Loaded Radius (mm) | 425 |
| Rolling Circumference (mm) | 2850 |
| SRI (mm) | 450 |
| Rim Rec | 16.00 |
| ECE | E11-106R-007767 |

Load capacity (Kg)

| km/h / bar | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.5 |
|------------|------|------|------|------|------|------|------|------|------|
| 65 | 1200 | 1450 | 1665 | 1940 | 2185 | 2400 | 2645 | 2895 | 3075 |
| 40 | 1635 | 1970 | 2260 | 2640 | 2975 | 3265 | 3600 | 3935 | 4185 |
| 30 | 1815 | 2185 | 2510 | 2930 | 3300 | 3625 | 3995 | 4370 | 4645 |
| 10 | 2160 | 2605 | 2990 | 3490 | 3930 | 4320 | 4765 | 5205 | 5535 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 4:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..