

W 207 - Especificaciones técnicas



Description

W 207 es el neumático BKT para las aplicaciones deportivas todo terreno. Gracias a la tecnología M+S y el particular dibujo, W 207 ofrece la máxima tracción en cualquier condición. Este neumático se caracteriza por su excelente resistencia a la perforación en los terrenos más difíciles.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Vehículo ATV

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | AT 24 X 10 - 11 |

Dimensions International Standard

| | |
|-----------------------|-----------------|
| Ply Rating | 6 |
| Section Width (mm) | 249 |
| Overall Diameter (mm) | 612 |
| Rim Rec | 8.0 AT |
| Rim Alt | 7.5 AT ; 8.5 AT |

Load capacity (Kg)

| | | |
|--|------------|------|
| | km/h / bar | 0.45 |
| | 80 | 180 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..