



W 207 - Ficha técnica

Description

W 207 es el neumático BKT para las aplicaciones deportivas todo terreno. Gracias a la tecnología M+S y el particular dibujo, W 207 ofrece la máxima tracción en cualquier condición. Este neumático se caracteriza por su excelente resistencia a la perforación en los terrenos más difíciles.



UM

US Standard

Construction

BIAS

Machinery

Agricultura: Vehículo ATV

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
AT 22 X 11 - 8	STANDARD	94001736	6	9.0 AT	8.5 AT	10.7	22.1	TL	E4-75R-0004984-01
AT 22 X 11 - 9	STANDARD	94001743	6	9.0 AT	8.5 AT	10.7	22.1	TL	E4-75R-0004985-01
AT 25 X 12 - 9	STANDARD	94001637	6	9.5 AT	9.0 AT ; 10.0 AT	11.8	24.9	TL	E11-75R-004629
AT 25 X 13 - 9	STANDARD	94001644	6	10.5 AT	10.0 AT	13	25	TL	
AT 22 X 11 - 10	STANDARD	94027057	6	9.0 AT	8.5 AT	10.7	22.1	TL	E4-75R-0006333
AT 22 X 7 - 10	STANDARD	94027064	6	5.5 AT	6.0 AT	7	22	TL	E4-75R-0006331
AT 22 X 8 - 10	STANDARD	94001750	6	6.5 AT	6.0 AT	8	22	TL	E4-75R-0004981-01
AT 23 X 10 - 10	STANDARD	94001491	6	8.0 AT	7.5 AT ; 8.5 AT	9.8	23.1	TL	
AT 23 X 7 - 10	STANDARD	94027071	6	5.5 AT	6.0 AT	7	23	TL	E4-75R-0006335
AT 23 X 8 - 10	STANDARD	94001514	6	6.5 AT	6.0 AT	8	23.2	TL	
AT 24 X 11 - 10	STANDARD	94001767	6	9.0 AT	8.5 AT	11	24	TL	E4-75R-0004987-01
AT 25 X 11 - 10	STANDARD	94001606	6	9.0 AT	8.5 AT	11.2	25.2	TL	E11-75R-004673
AT 25 X 12 - 10	STANDARD	94001620	6	9.5 AT	9.0 AT ; 10.0 AT	11.7	25.2	TL	
AT 23 X 8 - 11	STANDARD	94001521	6	6.5 AT	6.0 AT	8	23	TL	
AT 24 X 10 - 11	STANDARD	94001538	6	8.0 AT	7.5 AT ; 8.5 AT	9.8	24.1	TL	
AT 24 X 8 - 11	STANDARD	94001552	6	6.5 AT	6.0 AT	8	24.1	TL	
AT 24 X 9 - 11	STANDARD	94001576	6	7.0 AT	7.5 AT	8.9	24	TL	
AT 25 X 10 - 11	STANDARD	94001583	6	8.0 AT	7.5 AT ; 8.5 AT	9.8	25.1	TL	
AT 25 X 8 - 11	STANDARD	94001651	6	6.5 AT	6.0 AT	8	25.1	TL	
AT 24 X 8 - 12	STANDARD	94001569	6	6.5 AT	6.0 AT	7.8	24.2	TL	E11-75R-005007
AT 25 X 10 - 12	STANDARD	94001774	6	8.0 AT	6.5 AT ; 7.5 AT ; 8.5 AT	9.8	25.1	TL	E4-75R-0004991
AT 25 X 11 - 12	STANDARD	94001613	6	9.0 AT	8.5 AT	11.2	25.1	TL	E11-75R-004674
AT 25 X 8 - 12	STANDARD	94001781	6	6.5 AT	6.0 AT	7.8	25.1	TL	E4-75R-0004981-01
AT 26 X 10 - 12	STANDARD	94027088	6	8.0 AT	7.5 AT ; 8.5 AT	9.5	25.9	TL	E4-75R-0006336
AT 26 X 12 - 12	STANDARD	94027095	6	9.5 AT	8.0 AT ; 8.5 AT ; 9.0 AT	11.8	25.9	TL	E4-75R-0006337
AT 26 X 8 - 12	STANDARD	94043538	6	6.50 AT	6.00 AT	8	26	TL	E11-75R-005008
AT 27 X 10 - 12	STANDARD	94027101	6	8.0 AT	7.5 AT ; 8.5 AT	9.5	26.9	TL	E4-75R-0006338
AT 27 X 12 - 12	STANDARD	94027118	6	9.5 AT	8.5 AT ; 9.0 AT	11.8	26.9	TL	E4-75R-0006339
AT 28 X 10 - 12	STANDARD	94027125	6	8.0 AT	7.5 AT ; 8.5 AT	9.5	27.8	TL	E4-75R-0006340
AT 28 X 12 - 12	STANDARD	94027132	6	9.5 AT	8.5 AT ; 9.0 AT	11.8	27.8	TL	E4-75R-0006341

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..