

XL GRIP (T) - Ficha técnica



Description

XL GRIP (E-3) es ideal para utilizarlo en los camiones con volquetes que transportan cargas pesadas en las minas. La mezcla de la banda de rodadura ha sido desarrollada para minimizar el riesgo de cortes y perforaciones en los terrenos más difíciles. XL GRIP (E-3) ofrece una excepcional tracción, asegurando un ciclo de vida prolongado del neumático.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Volquete

| SIZE | Version | USACode | PR | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|------------|----------|----------|----|---------|---------|------|------|------|-------|------|
| 8.25 - 16 | STANDARD | 94060832 | 16 | 6.50 H | 6.00 G | 9.4 | 34.3 | 0 | 0 | TT |
| 10.00 - 20 | STANDARD | 94015665 | 18 | 7.5 | 7.0 | 11.2 | 42.3 | 19.9 | 128.2 | TT |
| 11.00 - 20 | STANDARD | 94029358 | 18 | 8.0 | 7.5 | 11.7 | 43.9 | 20.8 | 132.6 | TT |
| 12.00 - 20 | STANDARD | 94047789 | 18 | 8.5 | 8.0 | 12.6 | 45.5 | 21.5 | 136.4 | TT |
| 12.00 - 20 | STANDARD | 94047840 | 20 | 8.5 | 8.0 | 12.6 | 45.5 | 21.5 | 136.4 | TT |
| 12.00 - 20 | STANDARD | 94061914 | 24 | 8.5 | 8.0 | 12.6 | 45.5 | 21.5 | 136.4 | TT |
| 12.00 - 24 | STANDARD | 94015672 | 20 | 8.5 | 8.0 | 12.6 | 49.2 | 23 | 146.1 | TT |
| 12.00 - 24 | STANDARD | 94027590 | 20 | 8.5 | 8.0 | 12.6 | 49.2 | 23 | 146.1 | TL |
| 12.00 - 24 | STANDARD | 94031122 | 24 | 8.5 | 8.0 | 12.6 | 49.2 | 23 | 146.1 | TT |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 0:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..