

XL GRIP ULTRA - Ficha técnica



Description

XL GRIP ULTRA es un neumático de telas cruzadas proyectado para volquetes utilizados en condiciones de servicio pesado, como aplicaciones en la minería, en las conteras o en las obras de construcción. Este neumático se caracteriza por una robusta carcasa de nylon con juntas de conexión optimizadas así como una mezcla especial de la banda de rodadura para asegurar una elevada resistencia a los cortes y las laceraciones, durabilidad y resistencia al desgaste excelentes en combinación con extraordinarias propiedades de autolimpieza también en superficies rocosas.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Volquete

SIZE	Version	USACode	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
10.00 - 20	STANDARD	94064205	18	7.5	7.0	11.2	42.3	19.9	128.2	TT
11.00 - 20	STANDARD	94064212	18	8.0	7.5	11.7	43.9	20.8	132.6	TT
12.00 - 20	STANDARD	94069569	20	8.5	8.0	12.6	45.5	21.5	136.4	TT
12.00 - 24	INDUSTRIAL	94060856	24	8.5	8.0	12.6	49.2	23	146.1	TT
12.00 - 24	STANDARD	94057467	20	8.5	8.0	12.6	49.2	23	146.1	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..