

AGRI GRIP - Spécifications techniques



Description

AGRI GRIP est un pneu pour les opérations de transport et il est particulièrement approprié pour les applications avec remorques pour canne à sucre. AGRI GRIP est équipé d'une carcasse robuste qui offre une capacité de charge élevée en même temps qu'une excellente résistance aux coupures et lacérations. Le dessin particulier de la bande de roulement assure un long cycle de vie.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

| | |
|-----------|-----------|
| Version | DUAL BEAD |
| Type | TL |
| Tyre Size | 23.1 - 26 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94045747 |
| Ply Rating | 18 |
| Overall Width (inch) | 23.4 |
| Overall Diameter (inch) | 61.4 |
| Static Loaded Radius (inch) | 27.9 |
| Rolling Circumference (inch) | 183.4 |
| Rim Rec | DW 20 B |

Load capacity (lbs)

| | |
|-----------|-------|
| mph / psi | 38 |
| 20 FR LLV | 12350 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 12:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..