

AGRI TRAILER - Spécifications techniques



Description

AGRI TRAILER a été spécialement conçu pour les remorques de tracteur. Ce pneu est idéal pour l'agriculture moderne du fait qu'il convient aussi bien pour les de transport en assurant un cycle de vie plus long sur route que hors route. Sa construction robuste se traduit par une capacité de charge élevée, tandis que sa bande de roulement extra-profonde lui permet de faire plus de kilomètres.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

Dimensions International Standard

Ply Rating	18
Section Width (mm)	286
Overall Diameter (mm)	1080
Rim Rec	7.5
Rim Alt	7.0 ; 8.0

Load capacity (Kg)

	km/h / bar	9.30	8.60
30 LS		3845	-
30 LD		-	3405

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..