

## AGRIMAX ELOS - Spécifications techniques



### Description

AGRIMAX ELOS a été conçu pour assurer la plus grande traction même dans des conditions particulièrement difficiles sur terrains mouillés - tels les rizières - et marécageux. Le dessin de la bande de roulement a été élaboré spécialement pour garantir d'excellentes qualités d'auto-nettoyage, ce qui est fondamental lors des travaux dans les champs boueux et pendant les transferts. Pour optimiser la productivité de l'entreprise agricole, des bourrelets de protection sur les flancs ont été insérés dans le dessin du pneu AGRIMAX ELOS pour assurer à tout moment la plus grande protection contre d'éventuels dommages.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tracteur

|           |             |
|-----------|-------------|
| Version   | STANDARD    |
| Type      | TL          |
| Tyre Size | 710/70 R 38 |
| LI/SS     | 178 A8/B    |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94058617        |
| Section Width (inch)         | 28.2            |
| Overall Diameter (inch)      | 79.5            |
| Static Loaded Radius (inch)  | 36              |
| Rolling Circumference (inch) | 240.3           |
| Rim Rec                      | DW 23 B         |
| Rim Alt                      | DW 25 B         |
| ECE                          | E11-106R-004896 |
| TRA Code                     | R2              |

## Load capacity (lbs)

| mph / psi | 9    | 12   | 15    | 17    | 20    | 23    | 29    | 35    | 41    | 46    | 52    |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 6120 | 7110 | 8100  | 9260  | 10250 | 11240 | 12400 | 13060 | 14380 | 15540 | 16530 |
| 25        | 6120 | 7110 | 8100  | 9260  | 10250 | 11240 | 12400 | 13060 | 14380 | 15540 | 16530 |
| 20        | 6550 | 7620 | 8670  | 9910  | 10980 | 12040 | 13270 | 13980 | 15400 | 16630 | 17690 |
| 5 LT      | 8200 | 9530 | 10860 | 12410 | 13750 | 15070 | 16620 | 17500 | 19280 | 20830 | 22160 |
| 5 HT      | 6550 | 7620 | 8670  | 9910  | 10980 | 12040 | 13270 | 13980 | 15400 | 16630 | 17690 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..