

AGRIMAX RT 600 - Spécifications techniques

Description

AGRIMAX RT 600 est le pneu idéal pour les pelouses et les applications récolte et pulvérisation. Grâce à sa large zone de contact, AGRIMAX RT 600 garantit une répartition optimisée de la pression sur le terrain en réduisant les dommages sur les prairies et en protégeant le sol. Grâce à la technologie avec épaulement arrondi, la tringle renforcée et un nombre augmenté de crampons, ce pneu garantit une grande stabilité et une traction excellente.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Moissonneuse • Épandeur • Tracteur



Version	STANDARD
Type	TL
Tyre Size	650/75 R 32
LI/SS	172 A8/B

Dimensions US Standard

Usa code	94055968
Section Width (inch)	25.8
Overall Diameter (inch)	70.4
Static Loaded Radius (inch)	31.8
Rolling Circumference (inch)	213.2
Rim Rec	DW 21 B
Rim Alt	DW 20 B ; DW 23 B
ECE	E11-106R-004755

Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	46	49	55
30	6390	7360	9030	9870	10840	11810	12790	13890	-	-
25	6390	7360	9030	9870	10840	11810	12790	13890	-	-
20	6840	7880	9670	10560	11610	12640	13690	14870	-	-
5 LT	8560	9880	12100	13230	14530	15830	17130	18620	-	-
5 HT	6840	7880	9670	10560	11610	12640	13690	14870	-	-
5 Cyc.	-	10520	13460	14760	17120	18770	20550	22320	22670	23610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 12:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..