

## AGRIMAX RT 600 - Spécifications techniques

### Description

AGRIMAX RT 600 est le pneu idéal pour les pelouses et les applications récolte et pulvérisation. Grâce à sa large zone de contact, AGRIMAX RT 600 garantit une répartition optimisée de la pression sur le terrain en réduisant les dommages sur les prairies et en protégeant le sol. Grâce à la technologie avec épaulement arrondi, la tringle renforcée et un nombre augmenté de crampons, ce pneu garantit une grande stabilité et une traction excellente.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Moissonneuse • Épandeur • Tracteur



Version	STANDARD
Type	TL
Tyre Size	750/65 R 26
LI/SS	171 A8/B

## Dimensions International Standard

Section Width (mm)	750
Overall Diameter (mm)	1636
Static Loaded Radius (mm)	737
Rolling Circumference (mm)	4987
SRI (mm)	775
Rim Rec	DW 24 B
Rim Alt	DW 23 B ; DW 25 B
ECE	E11-106R-006182

## Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	2830	3260	3690	4000	4370	4860	5230	5720	6150	-	-
40	2830	3260	3690	4000	4370	4860	5230	5720	6150	-	-
30	3030	3495	3955	4285	4680	5205	5600	6125	6585	-	-
10 LT	3795	4370	4950	5360	5855	6515	7010	7670	8245	-	-
10 HT	3030	3495	3955	4285	4680	5205	5600	6125	6585	-	-
10 Cyc	-	5240	5930	6425	7015	7810	8400	9190	9880	10010	10455

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 12:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..