

## AGRIMAX RT 600 - Spécifications techniques

### Description

AGRIMAX RT 600 est le pneu idéal pour les pelouses et les applications récolte et pulvérisation. Grâce à sa large zone de contact, AGRIMAX RT 600 garantit une répartition optimisée de la pression sur le terrain en réduisant les dommages sur les prairies et en protégeant le sol. Grâce à la technologie avec épaulement arrondi, la tringle renforcée et un nombre augmenté de crampons, ce pneu garantit une grande stabilité et une traction excellente.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Moissonneuse • Épandeur • Tracteur



Version	STANDARD
Type	TL
Tyre Size	750/70 R 26
LI/SS	172 A8/B

## Dimensions US Standard

Usa code	94073146
Section Width (inch)	30.7
Overall Diameter (inch)	68.9
Static Loaded Radius (inch)	30.9
Rolling Circumference (inch)	207.4
Rim Rec	DW 25 B
Rim Alt	DW 24 B
ECE	E11-106R-007934

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46	52
30	5970	6940	7930	8900	9780	10840	11950	12640	13890	-	-
25	5970	6940	7930	8900	9780	10840	11950	12640	13890	-	-
20	6400	7440	8490	9520	10570	11610	12800	13550	14880	-	-
5 LT	8010	9310	10630	11930	13230	14540	16030	16950	18630	-	-
5 HT	6400	7440	8490	9520	10570	11610	12800	13550	14880	-	-
5 Cyc	-	11170	12730	14290	15850	17420	19200	20310	22320	22670	23610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 12:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..