

AGRIMAX RT 657 - Spécifications techniques



Description

AGRIMAX RT 657 est le pneu idéal pour le travail aux champs et pour l'utilisation sur route; certaines tailles conviennent également pour les vendanges. Ce pneu assure un excellent confort de conduite ainsi que des économies de carburant non négligeables. Il se distingue de par une grande capacité de charge à de vitesses élevées. Agrimax RT 657 représente la meilleure solution pour ceux qui ont besoin d'un pneu polyvalent et fiable sans pour autant compromettre les performances.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tracteur • Machine à vendanger

Version	STEEL BELTED
Type	TL
Tyre Size	650/65 R 38
LI/SS	178 A8/175 B

Dimensions US Standard

Usa code	94074853
Section Width (inch)	25.4
Overall Diameter (inch)	71.5
Static Loaded Radius (inch)	32.6
Rolling Circumference (inch)	216.1
Rim Rec	DW 20 B
Rim Alt	DW 21 B ; DW 23 B
ECE	E11-106R-008886
TRA Code	R1W

Load capacity (lbs)

mph / psi	51
30	15190
25	16540
20	17710
15	18370
5	24810
Static	38030
5 LT	23150
12 LT	19850
5 HT	17710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..