

AGRIMAX RT 657 - Spécifications techniques



Description

AGRIMAX RT 657 est le pneu idéal pour le travail aux champs et pour l'utilisation sur route; certaines tailles conviennent également pour les vendanges. Ce pneu assure un excellent confort de conduite ainsi que des économies de carburant non négligeables. Il se distingue de par une grande capacité de charge à de vitesses élevées. Agrimax RT 657 représente la meilleure solution pour ceux qui ont besoin d'un pneu polyvalent et fiable sans pour autant compromettre les performances.

UM

US Standard

Construction

RADIAL

Machinery

Agriculture: Tracteur • Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	900/55 R 38
LI/SS	179 D/181 A8

Dimensions US Standard

Usa code	94067534
Section Width (inch)	34.6
Overall Diameter (inch)	76.8
Static Loaded Radius (inch)	34.6
Rolling Circumference (inch)	230
Rim Rec	DW 27 B
Rim Alt	DW 30 B
ECE	E11-106R-006946
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41
40	7180	8380	9400	10590	11790	12980	14530	15550	17100
30	7540	8800	9880	11130	12390	13650	15260	16340	17940
25	7640	8920	10010	11280	12550	13820	15460	16560	18200
20	8260	9630	10810	12190	13570	14950	16710	17890	19650
5 LT	9620	11220	12600	14200	15810	17400	19470	20840	22890
5 HT	8260	9630	10810	12190	13570	14950	16710	17890	19650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..