

AGRIMAX RT 765 - Spécifications techniques



Description

AGRIMAX RT 765, un pneu de la série 70 de BKT, est idéal pour équiper les tracteurs les plus modernes utilisés dans les applications lourdes, telles que traitements de terrains, déplacements aux champs et sur route, vendange et pulvérisations. La large zone de contact garantit une traction et un confort optimaux sur toutes les surfaces et à tout moment. Le pneu se distingue de par ses excellentes qualités d'autonettoyage et le compactage du sol réduit. Deux tailles sont disponibles avec la technologie de ceintures en acier.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur • Tracteur • Machine à vendanger

| | |
|-----------|-------------|
| Version | SPECIAL |
| Type | TL |
| Tyre Size | 480/70 R 24 |
| LI/SS | 138 D |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94062270 |
| Section Width (inch) | 18.9 |
| Overall Diameter (inch) | 51.8 |
| Static Loaded Radius (inch) | 22.8 |
| Rolling Circumference (inch) | 153.3 |
| Rim Rec | W 15 L |
| Rim Alt | W 14 L ; W 16 L |
| ECE | E11-106R-005519 |
| TRA Code | R1W |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 40 | 2870 | 3340 | 3800 | 4280 | 4740 | 5200 |
| 30 | 3010 | 3510 | 4000 | 4490 | 4980 | 5470 |
| 25 | 3140 | 2650 | 4170 | 4670 | 5190 | 5700 |
| 20 | 3300 | 3840 | 4380 | 4920 | 5460 | 5990 |
| 5 LT | 3850 | 4480 | 5100 | 5730 | 6360 | 6980 |
| 5 HT | 3300 | 3840 | 4380 | 4920 | 5460 | 5990 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 13:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..