

AGRIMAX RT 855 - Spécifications techniques



Description

AGRIMAX RT 855 est un pneu caractérisé par une excellente traction et un grand confort. Il est conçu essentiellement pour le travail de la terre et les déplacements tant dans les champs que sur la route; certaines tailles sont également adaptées pour les applications de pulvérisation et le vendange. AGRIMAX RT 855 possède des excellentes qualités d'auto-nettoyage qui permettent de passer rapidement du travail aux champs aux déplacements sur route.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur • Tracteur • Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	460/85 R 30 (18.4 R 30)
LI/SS	156 A8/B

Dimensions US Standard

Usa code	94047765
Section Width (inch)	18.7
Overall Diameter (inch)	60.8
Static Loaded Radius (inch)	26.8
Rolling Circumference (inch)	179.6
Rim Rec	W 16 L
Rim Alt	W 14 L ; W 15 L
ECE	E11-106R-007812
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46
30	3440	4060	4670	5200	5820	6350	6970	7500	8200	8820
25	3440	4060	4670	5200	5820	6350	6970	7500	8200	8820
20	3680	4340	5000	5580	6230	6800	7460	8020	8780	9440
5 LT	4620	5450	6270	6980	7800	8510	9340	10050	10990	11820
5 HT	3680	4340	5000	5580	6230	6800	7460	8020	8780	9440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 11:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..