

AGRIMAX RT 855 - Spécifications techniques



Description

AGRIMAX RT 855 est un pneu caractérisé par une excellente traction et un grand confort. Il est conçu essentiellement pour le travail de la terre et les déplacements tant dans les champs que sur la route; certaines tailles sont également adaptées pour les applications de pulvérisation et le vendange. AGRIMAX RT 855 possède des excellentes qualités d'auto-nettoyage qui permettent de passer rapidement du travail aux champs aux déplacements sur route.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur • Tracteur • Machine à vendanger

Version	SPECIAL
Type	TL
Tyre Size	460/85 R 34 (18.4 R 34)
LI/SS	147 A8/B

Dimensions US Standard

Usa code	94046782
Section Width (inch)	18.7
Overall Diameter (inch)	64.8
Static Loaded Radius (inch)	28.4
Rolling Circumference (inch)	191.5
Rim Rec	W 16 L
Rim Alt	W 14 L ; W 15 L
ECE	E4-106R-000632
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	3740	4340	4950	5570	6170	6780
25	3740	4340	4950	5570	6170	6780
20	4000	4650	5310	5960	6610	7260
5 LT	5000	5820	6650	7460	8280	9090
5 HT	4000	4650	5310	5960	6610	7260

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 09:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..