

## AGRIMAX RT 855 - Spécifications techniques



### Description

AGRIMAX RT 855 est un pneu caractérisé par une excellente traction et un grand confort. Il est conçu essentiellement pour le travail de la terre et les déplacements tant dans les champs que sur la route; certaines tailles sont également adaptées pour les applications de pulvérisation et le vendange. AGRIMAX RT 855 possède des excellentes qualités d'auto-nettoyage qui permettent de passer rapidement du travail aux champs aux déplacements sur route.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Pulvérisateur • Tracteur • Machine à vendanger

Version	STEEL BELTED
Type	TL
Tyre Size	480/80 R 50 (18.4 R 50)
LI/SS	176 A8

## Dimensions International Standard

Section Width (mm)	489
Overall Diameter (mm)	2036
Static Loaded Radius (mm)	945
Rolling Circumference (mm)	6183
SRI (mm)	975
Rim Rec	DW 16 L
Rim Alt	DW 15 L ; W 15 L
ECE	E4-106R-001495
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4	5.0
50	2060	2365	2715	3065	3415	3765	4070	4375	4760	5185	5470	5825	6320	7100
40	2060	2365	2715	3065	3415	3765	4070	4375	4760	5185	5470	5825	6320	7100
30	2205	2530	2905	3280	3655	4030	4360	4685	5095	5550	5855	6235	6765	7600
10 LT	2760	3170	3640	4110	4575	5045	5455	5865	6380	6950	7330	7805	8470	9515
10 HT	2205	2530	2905	3280	3655	4030	4360	4685	5095	5550	5855	6235	6765	7600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 23:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..