

## AGRIMAX RT 855 - Spécifications techniques



### Description

AGRIMAX RT 855 est un pneu caractérisé par une excellente traction et un grand confort. Il est conçu essentiellement pour le travail de la terre et les déplacements tant dans les champs que sur la route; certaines tailles sont également adaptées pour les applications de pulvérisation et le vendange. AGRIMAX RT 855 possède des excellentes qualités d'auto-nettoyage qui permettent de passer rapidement du travail aux champs aux déplacements sur route.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Pulvérisateur • Tracteur • Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	480/80 R 50 (18.4 R 50)
LI/SS	159 A8/B

## Dimensions US Standard

Usa code	94029914
Section Width (inch)	19.3
Overall Diameter (inch)	80.2
Static Loaded Radius (inch)	37
Rolling Circumference (inch)	243.4
Rim Rec	DW 16 L
Rim Alt	DW 15 L ; W 15 L
ECE	E4-106R-001486
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	4540	5210	5990	6760	7530	8300	8970	9640
25	4540	5210	5990	6760	7530	8300	8970	9640
20	4860	5580	6400	7230	8060	8880	9610	10330
5 LT	6080	6990	8020	9060	10090	11120	12030	12930
5 HT	4860	5580	6400	7230	8060	8880	9610	10330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 23:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..