

AGRIMAX RT 955 - Spécifications techniques



Description

AGRIMAX RT 955 est un pneu radial BKT idéal pour les applications cultures en couloir, et certaines tailles conviennent même pour la pulvérisation et les vignes. Avec son épaulement arrondi, la bande de roulement assure d'excellentes performances en matière de traction, stabilité et qualités d'autonettoyage. Grâce à sa carcasse robuste, AGRIMAX RT 955 garantit une capacité de charge élevée.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur • Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	300/95 R 46 (12.4 R 46)
LI/SS	148D/151A8

Dimensions US Standard

Usa code	94076154
Section Width (inch)	11.6
Overall Diameter (inch)	68.4
Static Loaded Radius (inch)	32
Rolling Circumference (inch)	209.4
Rim Rec	W 9
Rim Alt	W 10 ; W 11 ; DW 10 ; DW 11
ECE	E11-106R-0010269
TRA Code	R1

Load capacity (lbs)

mph / psi	9	12	17	23	29	35	41	46	52	58
40	8110	8980	9850	10280	10860	11150	11440	12020	12600	13030
30	8770	9720	10640	11120	11740	12060	12370	12990	13630	14090
25	8940	9910	10860	11350	11990	12310	12630	13250	13900	14390
20	9120	10100	11070	11570	12220	12550	12870	13520	14170	14660
5	9650	10690	11710	12230	12920	13270	13610	14290	14980	15500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/02/2025 11:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..