

AGRIMAX RT 955 - Fiche de données



Description

AGRIMAX RT 955 est un pneu radial BKT idéal pour les applications cultures en couloir, et certaines tailles conviennent même pour la pulvérisation et les vignes. Avec son épaulement arrondi, la bande de roulement assure d'excellentes performances en matière de traction, stabilité et qualités d'autonettoyage. Grâce à sa carcasse robuste, AGRIMAX RT 955 garantit une capacité de charge élevée.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur • Machine à vendanger

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
210/90 R 24 (8.3 R 24)	STANDARD	R1	107 A8/B	W 7	W 6	214	1010	462	3027	475	TL	E4-106R-001818
210/95 R 28 (8.3 R 28)	STANDARD	R1	116 A8/B	W 7	W 6	214	1111	513	3364	525	TL	E4-106R-001819
210/95 R 32 (8.3 R 32)	STANDARD	R1	120 A8/B	W 7	W 6	214	1213	571	3703	575	TL	E4-106R-001391
230/95 R 32 (9.5 R 32)	STANDARD	R1	128 A8/B	W 7	W 8	228	1251	585	3810	600	TL	E4-106R-000764
270/95 R 32 (11.2 R 32)	STANDARD	R1	136 A8/B	W 9	W 8 ; W 10	275	1327	614	4076	625	TL	E4-106R-000776
230/95 R 36 (9.5 R 36)	STANDARD	R1	130 A8/B	W 7	W 8	228	1352	639	4112	650	TL	E4-106R-000765
270/80 R 36	STANDARD	R1	134 A8/B	W 9	W 8 ; W 10	275	1346	629	4090	650	TL	E11-106R-006758
270/95 R 36 (11.2 R 36)	STANDARD	R1	139 A8/B	W 9	W 8 ; W 10	275	1428	665	4335	675	TL	E4-106R-000659
270/95 R 38 (11.2 R 38)	STANDARD	R1	140 A8/B	W 9	W 8 ; W 10	275	1479	697	4510	700	TL	E4-106R-000657
230/95 R 40 (9.5 R 40)	STANDARD	R1	132 A8/B	W 7	W 8	228	1454	690	4445	700	TL	E11-106R-004066
230/95 R 42 (9.5 R 42)	STANDARD	R1	133 A8/B	W 7	W 8	228	1506	714	4595	725	TL	E4-106R-000772
300/85 R 42 (11.2 R 42)	STANDARD	R1	144 A8/B	W 9	W 10 ; W 11	295	1577	745	4850	750	TL	E4-106R-001396
210/95 R 44 (8.3 R 44)	STANDARD	R1	120 A8/B	W 7	W 6	214	1518	721	4653	725	TL	E4-106R-000771
230/95 R 44 (9.5 R 44)	STANDARD	R1	134 A8/B	W 7	W 8	228	1556	739	4788	750	TL	E4-106R-000777
270/95 R 44 (11.2 R 44)	STANDARD	R1	142 A8/B	W 9	W 8 ; W 10	275	1632	764	4983	775	TL	E4-106R-00784
270/95 R 46 (11.2 R 46)	STANDARD	R1	143 A8/B	W 9	W 8 ; W 10	275	1683	792	5169	800	TL	E4-106R-000785
300/95 R 46 (12.4 R 46)	STANDARD	R1	148 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1738	812	5318	825	TL	E4-106R-000790
340/85 R 46 (13.6 R 46)	STANDARD	R1	150 A8/B	W 12	W 11	353	1746	826	5346	850	TL	E4-106R-001828
230/95 R 48 (9.5 R 48)	STANDARD	R1	136 A8/B	W 7	W 8	228	1656	792	5085	825	TL	E4-106R-000778
230/95 R 48 (9.5 R 48)	STANDARD	R1	136D/139A8	W 7	W 8	228	1656	792	5085	825	TL	E11-106R-004067
270/95 R 48 (11.2 R 48)	STANDARD	R1	144 A8/B	W 9	W 8 ; W 10	275	1733	820	5351	825	TL	E4-106R-000782
340/85 R 48 (13.6 R 48)	STANDARD	R1	151D/154A8	W 12	W 11	353	1797	855	5572	875	TL	E11-106R-005765
340/85 R 48	STANDARD	R1	152 A8/B	W 12	W 11	353	1797	855	5572	875	TL	E4-106R-000800

(13.6 R 48)												
300/95 R 52 (12.4 R 52)	STANDARD	R1	151 A8/B	W9	W 10 ; W 11 ; DW 10 ; DW 11	295	1891	889	5774	900	TL	E4-106R-001484
270/95 R 54 (11.2 R 54)												
	STANDARD	R1	146 A8/B	W9	W 8 ; W 10	275	1885	894	5815	900	TL	E4-106R-001410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 23:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..