

AGRIMAX SPARGO - Spécifications techniques



Description

AGRIMAX SPARGO est le pneu BKT spécial pour les applications en couloirs, conçu pour améliorer la productivité du champ en préservant le sol à long terme. Il a d'excellentes propriétés d'auto-nettoyage et une capacité de charge supérieure à des pressions standard. AGRIMAX SPARGO garantit une excellente traction en même temps qu'une grande stabilité aux champs et lors des déplacements sur la route.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur

Version	STANDARD
Type	TL
Tyre Size	VF 320/90 R 50
LI/SS	169 D

Dimensions International Standard

Section Width (mm)	323
Overall Diameter (mm)	1846
Static Loaded Radius (mm)	865
Rolling Circumference (mm)	5650
SRI (mm)	875
Rim Rec	W 11
Rim Alt	W 10 ; DW 10 ; W 10 L ; DW 11
ECE	E11-106R-007204
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4	4.8
70	2415	2685	2955	3085	3220	3330	3435	3595	3760	3810	3865	4105	4350	4455	4565	4775	4990	5365
From 65 to 40	2610	2900	3190	3335	3480	3600	3715	3890	4060	4120	4180	4440	4700	4815	4930	5165	5395	5800
30	2665	2960	3260	3405	3555	3675	3790	3970	4145	4205	4265	4530	4800	4915	5035	5270	5510	5920
20	2720	3020	3320	3475	3625	3745	3865	4045	4225	4285	4350	4620	4890	5010	5130	5375	5615	6035
10	2875	3190	3510	3670	3830	3960	4085	4275	4470	4530	4595	4885	5170	5300	5425	5680	5935	6380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..