

## AGRIMAX SPARGO - Spécifications techniques



### Description

AGRIMAX SPARGO est le pneu BKT spécial pour les applications en couloirs, conçu pour améliorer la productivité du champ en préservant le sol à long terme. Il a d'excellentes propriétés d'auto-nettoyage et une capacité de charge supérieure à des pressions standard. AGRIMAX SPARGO garantit une excellente traction en même temps qu'une grande stabilité aux champs et lors des déplacements sur la route.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Pulvérisateur

|           |                    |
|-----------|--------------------|
| Version   | STANDARD           |
| Type      | TL                 |
| Tyre Size | VF 320/90 R 54 CFO |
| LI/SS     | 168 D              |

## Dimensions US Standard

|                              |                               |
|------------------------------|-------------------------------|
| Usa code                     | 94075249                      |
| Section Width (inch)         | 12.7                          |
| Overall Diameter (inch)      | 76.7                          |
| Static Loaded Radius (inch)  | 35.8                          |
| Rolling Circumference (inch) | 234.1                         |
| Rim Rec                      | W 11                          |
| Rim Alt                      | W 10 ; DW 10 ; W 10 L ; DW 11 |
| ECE                          | E11-106R-009070               |
| TRA Code                     | R1                            |

## Load capacity (lbs)

| mph / psi     | 14   | 17   | 20   | 23   | 26   | 29   | 32   | 35   | 38   | 41    | 44    | 47    | 49    | 52    | 55    | 58    | 61    | 64    |
|---------------|------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45            | 4920 | 5490 | 6180 | 6750 | 7090 | 7430 | 7670 | 7890 | 8290 | 8690  | 9030  | 9370  | 9660  | 9950  | 10230 | 10520 | 10970 | 11420 |
| From 40 to 25 | 5320 | 5940 | 6670 | 7290 | 7670 | 8030 | 8280 | 8530 | 8960 | 9400  | 9760  | 10130 | 10440 | 10750 | 11060 | 11370 | 11870 | 12350 |
| 20            | 5430 | 6060 | 6820 | 7450 | 7820 | 8190 | 8450 | 8700 | 9140 | 9580  | 9960  | 10340 | 10650 | 10970 | 11280 | 11600 | 12110 | 12600 |
| 12            | 5530 | 6180 | 6950 | 7590 | 7970 | 8360 | 8610 | 8870 | 9320 | 9770  | 10160 | 10540 | 10860 | 11180 | 11500 | 11820 | 12340 | 12850 |
| 5             | 5850 | 6530 | 7350 | 8020 | 8430 | 8830 | 9110 | 9390 | 9860 | 10330 | 10740 | 11150 | 11490 | 11820 | 12160 | 12500 | 13040 | 13580 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..