

AGRIMAX SPARGO - Spécifications techniques



Description

AGRIMAX SPARGO est le pneu BKT spécial pour les applications en couloirs, conçu pour améliorer la productivité du champ en préservant le sol à long terme. Il a d'excellentes propriétés d'auto-nettoyage et une capacité de charge supérieure à des pressions standard. AGRIMAX SPARGO garantit une excellente traction en même temps qu'une grande stabilité aux champs et lors des déplacements sur la route.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Pulvérisateur

Version	STANDARD
Type	TL
Tyre Size	VF 380/85 R 34
LI/SS	160 D

Dimensions International Standard

Section Width (mm)	380
Overall Diameter (mm)	1500
Static Loaded Radius (mm)	678
Rolling Circumference (mm)	4514
SRI (mm)	725
Rim Rec	W 13 A
Rim Alt	W 12
ECE	E11-106R-009071
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
70	2455	2745	3000	3165	3285	3410	3535	3705	3870	3995	4160
From 65 to 40	2655	2970	3240	3420	3555	3690	3825	4005	4185	4320	4500
30	2705	3030	3305	3490	3625	3765	3905	4085	4270	4410	4590
20	2760	3090	3370	3560	3695	3840	3980	4165	4355	4495	4680
10	2920	3265	3565	3765	3910	4060	4210	4405	4605	4755	4950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..