

AGRIMAX SPARGO - Spécifications techniques



Description

AGRIMAX SPARGO est le pneu BKT spécial pour les applications en couloirs, conçu pour améliorer la productivité du champ en préservant le sol à long terme. Il a d'excellentes propriétés d'auto-nettoyage et une capacité de charge supérieure à des pressions standard. AGRIMAX SPARGO garantit une excellente traction en même temps qu'une grande stabilité aux champs et lors des déplacements sur la route.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur

Version	STANDARD
Type	TL
Tyre Size	VF 380/90 R 46
LI/SS	175 D

Dimensions International Standard

Section Width (mm)	390
Overall Diameter (mm)	1852
Static Loaded Radius (mm)	848
Rolling Circumference (mm)	5582
SRI (mm)	900
Rim Rec	DW 13 B
Rim Alt	W 13 A ; DW 12
ECE	E11-106R-007527
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4	4.6
70	2835	3190	3485	3665	3480	3960	4080	4315	4495	4670	4850	5025	5145	5320	5440	5675	5915	6210
From 65 to 40	3120	3510	3835	4030	4225	4355	4485	4745	4940	5135	5330	5525	5655	5850	5980	6240	6500	6900
30	3180	3580	3910	4110	4305	4440	4570	4835	5035	5235	5435	5635	5765	5965	6095	6360	6630	7040
20	3240	3650	3985	4190	4390	4525	4660	4930	5135	5340	5540	5745	5880	6080	6215	6485	6760	7180
10	3430	3860	4215	4430	4645	4790	4930	5215	5430	5645	5860	6075	6220	6435	6575	6860	7150	7590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..