

AGRIMAX SPARGO - Spécifications techniques



Description

AGRIMAX SPARGO est le pneu BKT spécial pour les applications en couloirs, conçu pour améliorer la productivité du champ en préservant le sol à long terme. Il a d'excellentes propriétés d'auto-nettoyage et une capacité de charge supérieure à des pressions standard. AGRIMAX SPARGO garantit une excellente traction en même temps qu'une grande stabilité aux champs et lors des déplacements sur la route.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur

Version	STANDARD
Type	TL
Tyre Size	VF 380/90 R 50
LI/SS	175 D

Dimensions International Standard

Section Width (mm)	390
Overall Diameter (mm)	1950
Static Loaded Radius (mm)	893
Rolling Circumference (mm)	5950
SRI (mm)	925
Rim Rec	W13 B
Rim Alt	W12 B
ECE	E11-106R-006400
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	3010	3385	3700	3890	4075	4200	4325	4580	4765	4955	5145	5330	5455	5645	5770	6020	6275
From 65 to 40	3310	3725	4070	4275	4485	4620	4760	5035	5240	5450	5655	5865	6000	6210	6345	6620	6900
30	3375	3795	4150	4360	4570	4710	4850	5135	5345	5555	5765	5975	6120	6330	6470	6750	7035
20	3440	3870	4230	4445	4660	4805	4950	5235	5450	5665	5880	6095	6240	6455	6600	6885	7175
10	3640	4095	4475	4705	4930	5085	5235	5540	5765	5995	6220	6450	6600	6830	6980	7285	7590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..