

## AGRIMAX V-FLECTO - Spécifications techniques



### Description

AGRIMA V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'auto-nettoyage. Conçu avec la technologie VF exclusive, Agrimax V-FLECTO supporte des charges lourdes avec des pressions de gonflage plus basses à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 520/60 R 28 NRO
LI/SS	149 D

## Dimensions US Standard

Usa code	94060733
Section Width (inch)	20.3
Overall Diameter (inch)	52.6
Static Loaded Radius (inch)	23.1
Rolling Circumference (inch)	153.9
Rim Rec	DW 18 L
Rim Alt	W 18 L
Narrow Rim option	DW 16 L
ECE	E11-106R-005497
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
45	3570	4170	4750	5350	5920	6510
from 40 to 25	3940	4590	5220	5870	6510	7165
20	4010	4670	5320	5990	6640	7310
12	4090	4760	5420	6110	6770	7450
5	4320	5040	5740	6460	7160	7880
*Upto 5 Cyc with front loader	5500	6420	7310	8220	9120	10030
5 HT	4010	4670	5320	5990	6640	7310

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 10:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..