



# AGRIMAX V-FLECTO - Spécifications techniques



## Description

AGRIMAX V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'autonettoyage. Conçu avec la technologie VF exclusive, Agrimax V-FLECTO supporte des charges lourdes avec de pressions de gonflage plus basses à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

## UM

International Standard

## Construction

RADIAL

## Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 650/60 R 34
LI/SS	168 D

## Dimensions International Standard

<b>Section Width (mm)</b>	660
<b>Overall Diameter (mm)</b>	1676
<b>Static Loaded Radius (mm)</b>	750
<b>Rolling Circumference (mm)</b>	4996
<b>SRI (mm)</b>	775
<b>Rim Rec</b>	DW 23 B
<b>Rim Alt</b>	DW21B
<b>ECE</b>	E11-106R-007210

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0
<b>70</b>	2605	3010	3420	3880	4235	4590	5100
<b>From 65 to 40</b>	2860	3305	3755	4260	4650	5040	5600
<b>30</b>	2915	3375	3830	4345	4745	5145	5715
<b>20</b>	2975	3375	3830	4345	4745	5145	5715
<b>10</b>	3145	3635	4130	4685	5115	5545	6160
<b>*Upto 10 Cyc with front loader</b>	4000	4630	5255	5960	6510	7060	7840
<b>10 HT</b>	2915	3375	3830	4345	4745	5145	5715

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 06:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..