

AGRIMAX V-FLECTO - Spécifications techniques



Description

AGRIMA V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'auto-nettoyage. Conçu avec la technologie VF exclusive, Agrimax V-FLECTO supporte des charges lourdes avec des pressions de gonflage plus basses à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 710/70 R 38
LI/SS	181 D

Dimensions International Standard

Section Width (mm)	715
Overall Diameter (mm)	1961
Static Loaded Radius (mm)	843
Rolling Circumference (mm)	5773
SRI (mm)	925
Rim Rec	DW 24 B
Rim Alt	DW 23 B; DW 25 B
ECE	E11-106R-006163

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3750	4350	4950	5625	6225	6825	7505
From 65 to 40	4125	4785	5445	6185	6845	7505	8250
30	4205	4880	5550	6305	6980	7655	8415
20	4290	4975	5660	6430	7115	7805	8580
10	4535	5260	5985	6800	7525	8255	9075
*Upto 10 Cyc with front loader	5775	6695	7620	8655	9580	10505	11550
10 HT	4205	4880	5550	6305	6980	7655	8415

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 08:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..