

## AGRIMAX V-FLECTO - Spécifications techniques



### Description

AGRIMA V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'auto-nettoyage. Conçu avec la technologie VF exclusive, Agrimax V-FLECTO supporte des charges lourdes avec des pressions de gonflage plus basses à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 710/70 R 42
LI/SS	185 D

## Dimensions US Standard

Usa code	94066148
Section Width (inch)	28.1
Overall Diameter (inch)	81.1
Static Loaded Radius (inch)	36.3
Rolling Circumference (inch)	243.4
Rim Rec	DW 25 B
Rim Alt	DW 23 B; DW 24 B
ECE	E11-106R-006266

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	8730	10020	11510	13000	14470	15960	17450	18550
From 40 to 25	9590	11010	12640	14270	15910	17540	19170	20390
20	9780	11230	12900	14560	16230	17890	19550	20800
12	9980	11450	13150	14850	16540	18240	19940	21210
5	10550	12110	13910	15710	17500	19300	21090	22430
*Upto 5 Cyc with front loader	13430	15420	17700	19980	22280	24560	26840	28550
5 HT	9780	11230	12900	14560	16230	17890	19550	20800

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 06:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..