

AIROMAX AM 543 - Spécifications techniques



Description

AIROMAX AM 543 est le pneu idéal pour les applications avec grues dans le secteur bâtiment. Ce pneu fait preuve d'une excellente traction associée à une grande stabilité. Du fait que les pneus pour grues sont soumis à des sollicitations et à des conditions d'utilisation extrêmes, AIROMAX AM 543 a été conçu pour fournir une excellente résistance à la chaleur. De plus il convient pour toutes les opérations qui demandent un niveau de manœuvrabilité élevé.

UM

International Standard

Construction

 RADIAL

Machinery

Industriel: Grue automotrice

Version	STANDARD
Type	TL
Tyre Size	385/95 R 25 (14.00 R 25)
LI/SS	170 E

Dimensions International Standard

Overall Width (mm)	375
Overall Diameter (mm)	1355
Static Loaded Radius (mm)	627
Rolling Circumference (mm)	4156
Rim Rec	10.00/1.5

Load capacity (Kg)

km/h / bar	9.00
70	6000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 04:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..