

AIROMAX AM 28 WINTER - Spécifications techniques



Description

AIROMAX AM28 WINTER a été particulièrement conçu pour les grues mobiles à grande vitesse dans le secteur bâtiment. En effet, ce pneu BKT a été optimisé pour faire face aux tâches difficiles sur les chantiers de construction qui impliquent une manœuvrabilité précise à des vitesses élevées jusqu'à 80 km/h (50mph). AIROMAX AM28 WINTER a été réalisé avec un mélange particulièrement résistant à la chaleur - une caractéristique importante dans ce type d'environnements exigeants. Le dessin en blocs de la bande de roulement, spécialement conçue avec de multiples petites rainures dentelées, offre une adhérence et une traction exceptionnelles, évitant tout dérapage, même sur la neige ou la glace. En outre, le pneu garantit un confort de conduite exceptionnel et souple, même dans les conditions de service les plus sévères.

UM

International Standard

Construction

 RADIAL

Machinery

Industriel: Grue automotrice

Version	STANDARD
Type	TL
Tyre Size	445/95 R 25 (16.00 R 25)
LI/SS	174 F

Dimensions International Standard

Overall Width (mm)	435
Overall Diameter (mm)	1487
Static Loaded Radius (mm)	694
Rolling Circumference (mm)	4578
Rim Rec	11.25/2.0
Rim Alt	11.00/1.7 CR ; 11.00/1.7CRL
ECE	E4-54R-0022146

Load capacity (Kg)

km/h / bar	9.00
30	8500
40	7750
50	7500
60	7300
70	7100
80	6700
90	6300
100	5600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..