

## ARROW - Spécifications techniques



### Description

ARROW convient pour toutes les applications de transport avec remorques. Ce pneu a été conçu pour une utilisation essentiellement sur route et assure un kilométrage supérieur et un cycle de vie plus long. ARROW offre une capacité de charge élevée même à grande vitesse.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Remorque

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20

## Dimensions US Standard

Usa code	94022496
Ply Rating	16
Section Width (inch)	10.6
Overall Diameter (inch)	40.9
Rim Rec	7.0
Rim Alt	6.5 ; 7.5

## Load capacity (lbs)

mph / psi	-	-
-	-	-
-	-	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..