

ARROW - Fiche de données



Description

ARROW convient pour toutes les applications de transport avec remorques. Ce pneu a été conçu pour une utilisation essentiellement sur route et assure un kilométrage supérieur et un cycle de vie plus long. ARROW offre une capacité de charge élevée même à grande vitesse.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
6.50 - 14	STANDARD	10	4.5 J		175	695	TT	E4-54R-0024093
6.50 - 14 LT	HD	10	4.5 J		175	695	TT	
7.50 - 16	STANDARD	12	6.00 G	5.50 F	216	825	TT	
7.50 - 16	STANDARD	14	6.00 G	5.50 F	216	825	TT	
7.50 - 16	STANDARD	16	6.00 G	5.50 F	216	825	TT	
10.00 - 20	STANDARD	16	7.5	7.0 ; 8.0	286	1075	TT	
9.00 - 20	STANDARD	14	7.0	6.5 ; 7.5	270	1040	TT	
9.00 - 20	STANDARD	16	7.0	6.5 ; 7.5	270	1040	TT	
9.00 - 20	TRACTOR TRAILER	16	7.0	6.5 ; 7.5	270	1040	TT	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..