

AS 504 - Spécifications techniques



Description

AS 504 est un pneu agro-industriel essentiellement conçu pour les opérations de travail de la terre, de manutention de matériaux et les outils agricoles. Ce pneu qui se distingue de par ses excellentes propriétés d'auto-nettoyage et par une adhérence améliorée, est idéal pour les remorques aux champs et les chargeurs télescopiques. AS 504 est disponible en différentes versions pour répondre aux exigences spécifiques de l'utilisateur : une version « HD » avec mélange particulièrement résistant aux coupures et déchirures, tandis que une version « spécial » avec une carcasse renforcée qui assure un cycle de vie plus long.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Chargeuse télescopique • Remorque des champs

Industriel: Chargeuse télescopique

Version	SPECIAL
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	129 A8
LI/SS FREE ROLLING	142 A8

Dimensions US Standard

Usa code	94044177
Ply Rating	12
Section Width (inch)	12.1
Overall Diameter (inch)	38.9
Static Loaded Radius (inch)	17.2
Rolling Circumference (inch)	113.9
Rim Rec	W 9
Rim Alt	9 ; 11
ECE	E11-106R-004346

Load capacity (lbs)

mph / psi	54
5 FR	8180
15 FR	6960
20 FR	6550
25 FR	5840
5 DW	5710
15 DW	4850
20 DW	4560
25 DW	4080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 09:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..