

AS 504 - Spécifications techniques



Description

AS 504 est un pneu agro-industriel essentiellement conçu pour les opérations de travail de la terre, de manutention de matériaux et les outils agricoles. Ce pneu qui se distingue de par ses excellentes propriétés d'auto-nettoyage et par une adhérence améliorée, est idéal pour les remorques aux champs et les chargeurs télescopiques. AS 504 est disponible en différentes versions pour répondre aux exigences spécifiques de l'utilisateur : une version « HD » avec mélange particulièrement résistant aux coupures et déchirures, tandis que une version « spécial » avec une carcasse renforcée qui assure un cycle de vie plus long.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Chargeuse télescopique • Remorque des champs

Industriel: Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	15.5/80 - 24
LI/SS DRIVE WHEEL	145 A8
LI/SS FREE ROLLING	157 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	384
Overall Diameter (mm)	1262
Static Loaded Radius (mm)	570
Rolling Circumference (mm)	3875
SRI (mm)	600
Rim Rec	W 12
Rim Alt	W 13 ; W 14 L
ECE	E11-106R-003574

Load capacity (Kg)

	km/h / bar	3.00
	10 FR	5775
	25 FR	4910
	30 FR	4620
	40 FR	4125
	10 DW	4060
	25 DW	3450
	30 DW	3250
	40 DW	2900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 08:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..