

AT 108 - Fiche de données

Description

AT 108 est un pneu pour tous les types de terrain pour les véhicules ATV/VTT. Le dessin de la bande de roulement assure des performances et du confort exceptionnels tant sur route qu'aux champs.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Véhicule ATV



SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
AT 20 X 7 - 8	STANDARD	4	5.5 AT	6.0 AT	170	508	0	0	TL	E4-75R-0004980-01
AT 22 X 11 - 8	STANDARD	4	9.0 AT	8.5 AT	277	560	0	0	TL	E4-75R-0004983-01
AT 22 X 10 - 9	STANDARD	4	8.0 AT	7.5 AT ; 8.5 AT	254	559	0	0	TL	E4-75R-0004982
AT 22 X 11 - 9	STANDARD	4	9.0 AT	8.5 AT	275	557	0	0	TL	
AT 22 X 11 - 9	STANDARD	6	9.0 AT	8.5 AT	275	557	0	0	TL	E4-75R-0006332
AT 25 X 12 - 9	STANDARD	4	9.5 AT	9.0 AT ; 10.0 AT	292	640	0	0	TL	E11-75R-004654
AT 25 X 13 - 9	STANDARD	4	10.5 AT	10.0 AT	320	635	0	0	TL	E11-75R-004655
AT 25 X 13 - 9	STANDARD	6	10.5 AT	10.0 AT	320	635	0	0	TL	E11-75R-004656
AT 20 X 10 - 10	STANDARD	4	8.0 AT	7.5 AT ; 8.5 AT	250	514	235	1426	TL	E11-75R-004567
AT 20 X 10 - 10	STANDARD	8	8.0 AT	7.5 AT ; 8.5 AT	250	514	235	1526	TL	
AT 22 X 11 - 10	STANDARD	4	9.0 AT	8.5 AT	270	564	0	0	TL	E11-75R-005006
AT 22 X 11 - 10	STANDARD	6	9.0 AT	8.5 AT	270	564	0	0	TL	E4-75R-0006333
AT 22 X 8 - 10	STANDARD	4	6.5 AT	6.0 AT	206	557	0	0	TL	
AT 22 X 8 - 10	STANDARD	6	6.5 AT	6.0 AT	206	557	0	0	TL	E4-75R-0004981-01
AT 23 X 10 - 10	STANDARD	4	8.0 AT	7.5 AT ; 8.5 AT	259	594	0	0	TL	E11-75R-004658
AT 23 X 8 - 10	STANDARD	4	6.5 AT	6.0 AT	210	594	0	0	TL	E11-75R-004659
AT 24 X 11 - 10	STANDARD	6	9.0	8.5 AT	284	608	0	0	TL	
AT 24 X 11 - 10	STANDARD	4	9.0 AT	8.5 AT	284	608	0	0	TL	E4-75R-0004986
AT 25 X 12 - 10	STANDARD	4	9.5 AT	9.0 AT ; 10.0 AT	298	630	0	0	TL	E11-75R-004660
AT 25 X 12 - 10	STANDARD	6	9.5 AT	9.0 AT ; 10.0 AT	298	630	0	0	TL	
AT 22 X 7 - 11	STANDARD	4	5.5 AT		181	557	0	0	TL	E11-75R-004661
AT 23 X 8 - 11	STANDARD	4	6.5 AT	6.0 AT	191	594	0	0	TL	E11-75R-004662
AT 23 X 8 - 11	STANDARD	6	6.5 AT	6.0 AT	191	594	0	0	TL	
AT 24 X 10 - 11	STANDARD	4	8.0 AT	7.5 AT ; 8.5 AT	254	615	0	0	TL	E11-75R-004663
AT 24 X 8 - 11	STANDARD	4	6.5 AT	6.0 AT	206	610	0	0	TL	E11-75R-004664
AT 24 X 9 - 11	STANDARD	4	7.0 AT	7.5 AT	220	605	0	0	TL	E11-75R-004665
AT 24 X 9 - 11	STANDARD	6	7.0 AT	7.5 AT	220	605	0	0	TL	
AT 25 X 10 - 12	STANDARD	4	8.0 AT	6.5 AT ; 7.5 AT ; 8.5 AT	254	640	0	0	TL	E4-75R-0004990
AT 25 X 10 - 12	STANDARD	6	8.0 AT	6.5 AT ; 7.5 AT ; 8.5 AT	254	640	0	0	TL	E4-75R-0004991
AT 25 X 8 - 12	STANDARD	4	6.5 AT	6.0 AT	212	630	0	0	TL	E4-75R-0004988
AT 25 X 8 - 12	STANDARD	6	6.5 AT	6.0 AT	212	630	0	0	TL	E4-75R-0004989-01

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..