

AT 110 - Spécifications techniques



Description

AT 110 est le pneu BKT parfaitement adapté pour les applications Tout Terrain avec les véhicules ATV/VT. Grâce au contrôle excellent de la direction, AT 110 est le pneu idéal pour les essieux avant de votre véhicule. p;

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Véhicule ATV

Version	STANDARD
Type	TL
Tyre Size	AT 22 X 8 - 10

Dimensions International Standard

Ply Rating	4
Section Width (mm)	204
Overall Diameter (mm)	548
Rim Rec	6.5 AT
Rim Alt	6.0 AT

Load capacity (Kg)

km/h / bar	0.35
80	109

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..