

## AT 111 - Spécifications techniques

### Description

AT 111 convient pour les applications sportives Tout Terrain avec les véhicules ATV/VTT. Pour les utilisateurs qui ont besoin d'une traction et d'une durabilité plus élevées, une version "HD" avec bande de roulement profonde est disponible.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Véhicule ATV



Version	STANDARD
Type	TL
Tyre Size	AT 18 X 10 - 8

## Dimensions US Standard

Usa code	94000845
Ply Rating	2
Section Width (inch)	10
Overall Diameter (inch)	18
Rim Rec	8.0 AT
Rim Alt	7.5 AT ; 8.5 AT

## Load capacity (lbs)

mph / psi	4
50	185

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 04:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..